



## TABLA DE DIMENSIONAMIENTO

Tanque	E/S	D	Zeosorb® Pies <sup>3</sup>	Flujo GPM			Retrolavado	
				Lento <sup>(1)</sup>	Normal <sup>(2)</sup>	Pico <sup>(3)</sup>	Mínima	Máxima
9"x48"	1"	0.75"	1	3.5	5.3	7.1	4.4	8.8
10"x54"	1"	0.75"	1.5	4.4	6.5	8.7	5.5	11
12"x52"	1"	0.75"	2	6.3	9.4	12.6	7.9	16
13"x54"	1"	1"	2.5	7.4	11	15	9.2	18
14"x65"	1.25"	1"	3	9	13	17	11	21
16"x65"	1.25"	1"	4	11	17	22	14	28
18"x65"	1.25"	1"	5	14	21	28	18	35
21"x62"	1.25"	1.5"	7	19	29	38	24	48
24"x72"	1.5"	1.5"	10	25	38	50	31	63
30"x72"	2"	2"	15	39	59	79	49	98
36"x72"	2"	2.5"	20	57	85	113	71	141
42"x72"	2"	3"	30	77	115	154	96	192
48"x72"	3"	4"	40	101	151	201	126	251

**1** Calculado en base de 8 gpm/pie<sup>2</sup>, para aguas residuales tratadas, agua con gran cantidad de sólidos suspendidos, etc.

**2** Calculado en base de 12 gpm/pie<sup>2</sup>, para agua de buena calidad, pre-tratamiento de ósmosis inversa, potabilización de aguas.

**3** Calculado en base de 16 gpm/pie<sup>2</sup>, para aguas de excelente calidad, picos intermitentes de flujo durante el día.